

U.S.S.N. 10/015,419

CLAIMS:

Please amend the claims as follows:

1. (Currently Amended) An audio detection circuit comprising:
 - a. an audio signal;
 - b. a ~~means of circuit capable of~~ converting the audio signal to a pulse train having a frequency proportional to a frequency of the audio signal; and
 - c. an amplification ~~means circuit~~ coupled to the ~~means of circuit capable of~~ converting the audio signal to a pulse train;wherein the amplification ~~means circuit~~ is actuated when the pulse train has a frequency above a predetermined threshold.
2. (Currently Amended) The circuit of claim 1, further comprising a logic array coupled between the ~~means of circuit capable of~~ converting the audio signal to a pulse train, the logic array having an enable control coupled to a clock signal having a predetermined frequency.
3. (Original) The circuit of claim 2, wherein the logic array comprises a ripple counter.
4. (Currently Amended) An audio detection circuit comprising:
 - a. an audio signal;
 - b. a means of comparing the audio signal to a threshold signal, wherein the means of comparing generates a pulse train having a frequency proportional to the audio signal;
 - c. a logic array coupled to the means of comparing, the logic array having an enable control, wherein the logic array is responsive to the pulse train when the enable control is active;
 - d. a clock signal having a predetermined frequency and duty cycle coupled to the enable control of the logic array; and

U.S.S.N. 10/015,419

- c. a means for amplifying the audio signal, the means for amplifying having an enable input, wherein the enable input is coupled to the logic array; wherein the enable input of the amplifying means is actuated when the audio signal has a frequency component above a predetermined frequency threshold.
5. (Original) The circuit of claim 4, further comprising a delay circuit coupled to the enable input of the amplifying means.
6. (Original) The circuit of claim 5, wherein the logic array comprises a ripple counter.
7. (Original) The circuit of claim 6, wherein the ripple counter comprises at least two flip-flop circuits.
8. (Original) The circuit of claim 7, further comprising a loudspeaker coupled to the amplifying means.
9. (Original) The circuit of claim 8, wherein the predetermined threshold is at least 217 Hz.
10. (Original) An audio detection circuit comprising:
- a. an audio signal;
 - b. a first amplifier coupled to the audio signal;
 - c. a comparator having a reference voltage coupled to the first amplifier, wherein the comparator generates a pulse train proportional to the frequency of the audio signal;
 - d. a ripple counter coupled to the comparator, the ripple counter having an enable control, wherein the ripple counter is responsive to the pulse train when the enable control is active;
 - e. a clock having a predetermined frequency and duty cycle coupled to the enable control of the ripple counter; and
 - f. a second amplifier having an enable input, the enable input being coupled to the ripple counter;

U.S.S.N. 10/015,419

wherein the enable input of the second amplifier is actuated when the audio signal has a frequency component above a predetermined frequency threshold.